

NEK 400:2010

Jordfeilautomat 2P, B karakteristikk (ref temp 30 °C)

Elnr.	Type	I ₁	I ₂	Forlegningstype		Kabel mm ²
				A1	A2	
1612731	10A	1,13	1,40	Ok	Ok	1,5 mm ²
1612732	13A	1,13	1,42	Ok	Ok	2,5 mm ²
1611899	15A	1,13	1,30	Ok	-	2,5 mm ²
1612733	16A	1,13	1,45	-	-	2,5 mm ²
1612733	16A	1,13	1,45	Ok	Ok	4,0 mm ²
1612734	20A	1,13	1,30	Ok	-	4,0 mm ²

Jordfeilautomat 2P, C karakteristikk (ref temp 30 °C)

Elnr.	Type	I ₁	I ₂	Forlegningstype		Kabel mm ²
				A1	A2	
1606401	10A	1,13	1,40	Ok	Ok	1,5 mm ²
1612723	13A	1,13	1,42	Ok	Ok	2,5 mm ²
1611898	15A	1,13	1,30	Ok	-	2,5 mm ²
1606402	16A	1,13	1,45	-	-	2,5 mm ²
1606402	16A	1,13	1,45	Ok	Ok	4,0 mm ²
1606403	20A	1,13	1,30	Ok	-	4,0 mm ²

Jordfeilautomat 3P, C karakteristikk (ref temp 30 °C)

Elnr.	Type	I ₁	I ₂	Forlegningstype		Kabel mm ²
				A1	A2	
1606453	10A	1,13	1,30	Ok	Ok	1,5 mm ²
1611254	13A	1,13	1,35	Ok	Ok	2,5 mm ²
1606454	16A	1,13	1,43	Ok	Ok	4,0 mm ²